

Introduction to Cryptography
CS 236
On-Line MS Program
Networks and Systems Security
Peter Reiher

Outline

- What is data encryption?
- Cryptanalysis
- Basic encryption methods
 - Substitution ciphers
 - Permutation ciphers

Introduction to Encryption

- Much of computer security is about keeping secrets
- One method is to make the secret hard for others to read
- While (usually) making it simple for authorized parties to read

Encryption

- Encryption is the process of hiding information in plain sight
- Transform the secret data into something else
- Even if the attacker can see the transformed data, he can't understand the underlying secret

Encryption and Data Transformations

- Encryption is all about transforming the data
- One bit or byte pattern is transformed to another bit or byte pattern
- Usually in a reversible way

Encryption Terminology

- Encryption is typically described in terms of sending a message
 - Though it's used for many other purposes
- The sender is S
- The receiver is R
- And the attacker is O

More Terminology

- *Encryption* is the process of making message unreadable/unalterable by O
- *Decryption* is the process of making the encrypted message readable by R
- A system performing these transformations is a *cryptosystem*
 - Rules for transformation sometimes called a *cipher*

Plaintext and Ciphertext

- *Plaintext* is the original form of the message (often referred to as P)

```
Transfer  
$100 to my  
savings  
account
```

- *Ciphertext* is the encrypted form of the message (often referred to as C)

```
Sqzmredq  
#099 sn lx  
rzuhmfr  
zbbntms
```


Very Basics of Encryption Algorithms

- Most algorithms use a *key* to perform encryption and decryption
 - Referred to as K
- The key is a secret
- Without the key, decryption is hard
- With the key, decryption is easy

Terminology for Encryption Algorithms

- The encryption algorithm is referred to as $E()$
- $C = E(K, P)$
- The decryption algorithm is referred to as $D()$
 - Sometimes the same algorithm as $E()$
- The decryption algorithm also has a key

Symmetric and Asymmetric Encryption Systems

- Symmetric systems use the same keys for E and D :

$$P = D(K, C)$$

$$\text{Expanding, } P = D(K, E(K, P))$$

- Asymmetric systems use different keys for E and D:

$$C = E(K_E, P)$$

$$P = D(K_D, C)$$

Characteristics of Keyed Encryption Systems

- If you change only the key, a given plaintext encrypts to a different ciphertext
 - Same applies to decryption
- Decryption should be hard without knowing the key

Cryptanalysis

- The process of trying to break a cryptosystem
- Finding the meaning of an encrypted message without being given the key
- To build a strong cryptosystem, you must understand cryptanalysis

Forms of Cryptanalysis

- Analyze an encrypted message and deduce its contents
- Analyze one or more encrypted messages to find a common key
- Analyze a cryptosystem to find a fundamental flaw

Breaking Cryptosystems

- Most cryptosystems are breakable
- Some just cost more to break than others
- The job of the cryptosystem designer is to make the cost infeasible
 - Or incommensurate with the benefit extracted

Types of Attacks on Cryptosystems

- Ciphertext only
- Known plaintext
- Chosen plaintext
 - Differential cryptanalysis
- Algorithm and ciphertext
 - Timing attacks
- In many cases, the intent is to guess the key

Ciphertext Only

- No *a priore* knowledge of plaintext
- Or details of algorithm
- Must work with probability distributions, patterns of common characters, etc.
- Hardest type of attack

Known Plaintext

- Full or partial
- Cryptanalyst has matching sample of ciphertext and plaintext
- Or may know something about what ciphertext represents
 - E.g., an IP packet with its headers

Chosen Plaintext

- Cryptanalyst can submit chosen samples of plaintext to the cryptosystem
- And recover the resulting ciphertext
- Clever choices of plaintext may reveal many details
- Differential cryptanalysis iteratively uses varying plaintexts to break the cryptosystem
 - By observing effects of controlled changes in the offered plaintext

Algorithm and Ciphertext

- Cryptanalyst knows the algorithm and has a sample of ciphertext
- But not the key, and cannot get any more similar ciphertext
- Can use “exhaustive” runs of algorithm against guesses at plaintext
- Password guessers often work this way
- *Brute force attacks* – try every possible key to see which one works

Timing Attacks

- Usually assume knowledge of algorithm
- And ability to watch algorithm encrypting/decrypting
- Some algorithms perform different operations based on key values
- Watch timing to try to deduce keys
- Successful against some smart card crypto
- Similarly, observe power use by hardware while it is performing cryptography