

More Security Protocols CS 239 Security for System Software April 22, 2002

CS 239, Spring 2002

Lecture 7
Page 1

Outline

- Combining key distribution and authentication
- Verifying security protocols

CS 239, Spring 2002

Lecture 7
Page 2

Combined Key Distribution and Authentication

- Usually the first requires the second
 - Not much good to be sure the key is a secret if you don't know who you're sharing it with
- How can we achieve both goals?
 - In a single protocol
 - With relatively few messages

CS 239, Spring 2002

Lecture 7
Page 3


Needham-Schroeder Key Exchange

- Uses symmetric cryptography
- Requires a trusted authority
 - Who takes care of generating the new key
- More complicated than some protocols we've seen

CS 239, Spring 2002

Lecture 7
Page 4

Needham-Schroeder, Step 1



CS 239, Spring 2002







Lecture 7
Page 5

What's the Point of R_A ?

- R_A is random number chosen by Alice for this invocation of the protocol
 - Not used as a key, so quality of Alice's random number generator not too important
- Helps defend against replay attacks

CS 239, Spring 2002

Lecture 7
Page 6




Mallory Causes Problems

- Alice and Bob do something Mallory likes
- Mallory watches the messages they send to do so
- Mallory wants to make them do it again
- Can Mallory replay the conversation?
 - Let's try it without the random numbers

CS 239, Spring 2002

Lecture 7
Page 13

Mallory Waits For His Chance



CS 239, Spring 2002

Lecture 7
Page 14


What Will Alice Do Now?

- The message could only have been created by Trent
- It properly indicates she wants to talk to Bob
- It contains a perfectly plausible key
- Alice will probably go ahead with the protocol

CS 239, Spring 2002

Lecture 7
Page 15

The Protocol Continues



CS 239, Spring 2002

Lecture 7
Page 16


So What's the Problem

- Alice and Bob agree K_S is their key
 - They both know the key
 - Trent definitely created the key for them
 - Nobody else has the key
- But . . .

CS 239, Spring 2002

Lecture 7
Page 17

Mallory Steps Back Into the Picture



CS 239, Spring 2002

Lecture 7
Page 18


How Do the Random Numbers Help?

- Alice's random number assures her that the reply from Trent is fresh
- But why does Bob need another random number?

CS 239, Spring 2002


Lecture 7
Page 19

Why Bob Also Needs a Random Number



Let's say Alice doesn't want to talk to Bob


But Mallory wants Bob to think Alice wants to talk



CS 239, Spring 2002

Lecture 7
Page 20

So What?



Mallory can now play back an old message from Alice to Bob
And Bob will have no reason to be suspicious

Bob's random number exchange assured him that Alice really wanted to talk

CS 239, Spring 2002

Lecture 7
Page 21


So, Everything's Fine, Right?

- Not if any key K_S ever gets divulged
- Once K_S is divulged, Mallory can forge Alice's response to Bob's challenge
- And convince Bob that he's talking to Alice when he's really talking to Mallory

CS 239, Spring 2002

Lecture 7
Page 22

Mallory Cracks an Old Key



Mallory enlists 10,000 computers belonging to 10,000 grandmothers to crack K_S
Unfortunately, Mallory knows K_S
So Mallory can answer Bob's challenge

CS 239, Spring 2002

Lecture 7
Page 23

Timestamps in Security Protocols

- One method of handling this kind of problem is timestamps
- Proper use of timestamps can limit the time during which an exposed key is dangerous
- But timestamps have their own problems

CS 239, Spring 2002

Lecture 7
Page 24


Using Timestamps in the Needham-Schroeder Protocol

- The trusted authority includes timestamps in his encrypted messages to Alice and Bob
- Based on a global clock
- When Alice or Bob decrypts, if the timestamp is too old, abort the protocol

CS 239, Spring 2002

Lecture 7
Page 25

Using Timestamps to Defeat Mallory



CS 239, Spring 2002

Lecture 7
Page 26

Problems With Using Timestamps

- They require a globally synchronized set of clocks
 - Hard to obtain, often
 - Attacks on clocks become important
- They leave a window of vulnerability

CS 239, Spring 2002

Lecture 7
Page 27

The Suppress-Replay Attack

- Assume two participants in a security protocol
 - Using timestamps to avoid replay problems
- If the sender's clock is ahead of the receiver's, attacker can intercept message
 - And replay later, when receiver's clock still allows it

CS 239, Spring 2002

Lecture 7
Page 28


Handling Clock Problems

- 1). Rely on clocks that are fairly synchronized and hard to tamper
 - Perhaps GPS signals
- 2). Make all comparisons against the same clock
 - So no two clocks need to be synchronized

CS 239, Spring 2002







Lecture 7
Page 29

Neuman-Stubblebine Protocol,



CS 239, Spring 2002

Lecture 7
Page 30



Verifying Security Protocols

- Security protocols are obviously very complicated
- And any flaw in the protocol can be very expensive
- Thus, verifying their correctness is of great value
- How to do it?

CS 239, Spring 2002

Lecture 7
Page 37

Basic Approaches to Verifying Protocols

- Use standard specification and verification languages and tools
- Use expert systems
- Use logics for the analysis of knowledge and beliefs
- Use formal methods based on algebraic term-rewriting properties of cryptography

CS 239, Spring 2002

Lecture 7
Page 38

Using Standard Specification and Verification Tools

- Treat protocol as a computer program and prove its correctness
- The oldest approach
- Using
 - Finite state machines
 - First-order predicate calculus
 - Specification languages

CS 239, Spring 2002

Lecture 7
Page 39

Problems With the Approach

- Very laborious
- Worse, correctness isn't the same as security
 - The correctness you prove may not have even considered the possibility of certain attacks
- Too many protocols that have been "proven" have had security problems

CS 239, Spring 2002

Lecture 7
Page 40

Using Expert Systems

- Develop an expert system that knows a lot about security protocols
- Run it against proposed protocols
- In particular, use the expert system to determine if the protocol can reach an undesirable state
 - Such as exposing a secret key

CS 239, Spring 2002

Lecture 7
Page 41

Problems With the Expert System Approach

- Good at identifying flaws
 - Provided they are based on already known problems
- Not so good at proving correctness or security
- Or at uncovering flaws based on new attacks

CS 239, Spring 2002

Lecture 7
Page 42

Using Belief and Knowledge Logics

- An increasingly popular approach
- Describe certain properties that a security protocol should have
- Use logic to demonstrate the presence (or absence) of those properties

CS 239, Spring 2002

Lecture 7
Page 43

BAN Logic

- Named for its creators (Burrows, Abadi, and Needham)
- The most popular method of this kind
- Used to reason about authentication
 - Not other aspects of security
- Allows reasoning about beliefs in protocols

CS 239, Spring 2002

Lecture 7
Page 44

Sample BAN Logic Statements

- Alice believes X.
- Alice sees X.
- Alice said X.
- X is fresh.

CS 239, Spring 2002

Lecture 7
Page 45

Steps in Applying BAN Logic

- Convert protocol to an idealized form
- Add all assumptions about initial state
- Attach logical formulae to the statements
- Apply logical postulates to the assertions and assumptions to discover the beliefs of protocol parties

CS 239, Spring 2002

Lecture 7
Page 46

What Can BAN Logic Do?

- Discover flaws in protocols
 - Found flaws in Needham-Schroeder
- Discover redundancies
 - In Needham-Schroeder, Kerberos, etc.

CS 239, Spring 2002

Lecture 7
Page 47

Critiques of BAN Logic

- Translations into idealized protocols may not reflect the real protocol
- Doesn't address all important security issues for protocols
- Some feel that BAN logic can deduce characteristics that are obviously false

CS 239, Spring 2002

Lecture 7
Page 48

Using Algebraic Term-Rewriting Modeling Methods

- Model the protocol as an algebraic system
- Express the state of the participants' knowledge about the protocol
- Analyze the attainability of certain states

CS 239, Spring 2002

Lecture 7
Page 49

Use of These Methods

- NRL Protocol Analyzer
 - Has discovered flaws in several protocols
- A relatively new method
- Weakest link seems to be formalizing protocol into an algebraic system

CS 239, Spring 2002

Lecture 7
Page 50

Specialized Approaches

- Stubblebine & Gligor's method of modeling weak crypto checksums
 - Found problems in Kerberos and Privacy-Enhanced Mail
 - Not useful for other types of analysis
- Woo-Lam's approach for key distribution protocols
- Pfizmann's method for digital signatures
- There are others

CS 239, Spring 2002

Lecture 7
Page 51

An Entirely Different Approach

- Instead of using formal methods to verify security protocols,
- Use them to develop such protocols
- Some early work done using this approach
- Not clear if it will be fruitful

CS 239, Spring 2002

Lecture 7
Page 52

Bottom Line on Security Protocol Analysis

- Has been successful in finding some problems
- No one believes existing methods can find all problems
- Some knowledgeable observers think no method will ever be able to find all problems
- So, a useful tool, but not a panacea
- Research in this area continues

CS 239, Spring 2002

Lecture 7
Page 53